## **AMENDMENTS TO THE CLAIMS:**

Without prejudice, this listing of the claims replaces all prior versions and listings of the claims in the present application:

## **LISTING OF CLAIMS:**

1. (Currently Amended) A device for controlling a speed of a motor vehicle in terms of one of (a) a constant distance control in the case that at least one preceding vehicle is detected by a radar sensor and (b) a constant speed control in the case that no preceding vehicle is detected by a radar sensor, the device comprising:

an arrangement for allowing a distance to a preceding vehicle to be set by a driver of the vehicle in the form of a time gap; and

an arrangement for changing longitudinal dynamics of the speed control when the time gap changes;

an arrangement for increasing, given a decrease in the time gap, at least one of a maximum possible vehicle acceleration and a maximum possible vehicle deceleration implementable by a speed control system so that the vehicle is capable of at least one of accelerating and decelerating more quickly given the decrease in the time gap; and

an arrangement for first activating, given the decrease in the time gap, deceleration devices of the vehicle at a shorter distance from the preceding vehicle.

- 2. (Original) The device according to claim 1, wherein a change in the time gap allows different driving programs to be selected.
- 3. (Canceled)
- 4. (Canceled)
- 5. (Currently Amended) A method for controlling a speed of a motor vehicle in terms of one of (a) a constant distance control in the case that at least one preceding vehicle is detected by a radar sensor and (b) a constant speed control in the case that no preceding vehicle is detected by a radar sensor, the method comprising:

setting a distance to a preceding vehicle by a driver of the vehicle in the form of a time gap; and

changing longitudinal dynamics of the speed control when the time gap changes;

increasing, given a decrease in the time gap, at least one of a maximum possible vehicle acceleration and a maximum possible vehicle deceleration implementable by a speed control system so that the vehicle is capable of at least one of accelerating and decelerating more quickly given the decrease in the time gap; and

first activating, given the decrease in the time gap, deceleration devices of the vehicle at a shorter distance from the preceding vehicle.